

ADMtime IT Solutions

ADMtime IT Solutions

HP R/T3000 G2 2U L620 High Voltage NA/JP Uninterruptible Power S

585 000.00 ₸, ₸³.



Â

Battery type	Maintenance-free, sealed, valve-regulated lead acid (VRLA)
Communications serial ports	Standard DB-9 and USB port. Optional HP UPS Network Module
Communications software	HP Power Protector
Electrical input connection	NEMA L6-20P
Electrical output connections	(6) IEC 60320 C13; (2) IEC 60320 C19; (1) NEMA L6-20R

Environmental Compliance	No
Hot-swap batteries	Yes
Load segments	2
Operating voltage	200-208V
Power Availability	3000 W (maximum)
Product dimensions (W x D x H)	17.5 x 25 x 3.5 in
Weight (Imperial)	82 lb

Extended specifications

Technical Information

Plug/Connector Type	NEMA L6-20P
Receptacles	1 x IEC 60320 C13 6 x IEC 60320 C19 2 x NEMA L6-20R

Power Description

Load Capacity (VA)	3300 VA
Load Capacity (Watt)	3000 W

Management

Network Management	SNMP Manageable
--------------------	-----------------

Interfaces/Ports

Serial Port	Yes
-------------	-----

Battery Information

Battery Characteristics	Maintenance-free, Sealed
Battery Chemistry	Valve-regulated Lead Acid (VRLA)
Backup/Run Time (Full Load)	4 Minute
Backup/Run Time (Half Load)	12 Minute
Maximum Battery Recharge Time	48 Hour

Physical Characteristics

Form Factor	Tower/Rack Mountable
Height	3.5"
Width	17.5"
Depth	25"
Rack Height	2U

Miscellaneous

Certifications & Standards UL cUL UL1778 UL60950-1 CSA22.2 No.107.3-05 EN60950-1 IEC62040-1-1 NEC code 645-10 NEC code 645-11
Green Compliant Yes

Warranty

[D`D½Ñ,,D¾Ñ€D¼D°Ñ†D,Ñ• D¾ D¿Ñ€D¾D´D°D²Ñ†Dµ](#)

**DœD½DµD½D,Ñ• D¿D¾D°ÑfD¿D°Ñ,DµD»DµD¹: D•Ñ%oDµ D½DµÑ, D¼D½DµD½D,D¹ D¾D± Ñ•Ñ,D¾D¼Ñ,D¾D²D°Ñ€Dµ.
DÿD¾D¶D°D»ÑfD¹Ñ•Ñ,D°, D²D¾D¹D´D,Ñ,Dµ, Ñ‡Ñ,D¾D±Ñ‹ D¾Ñ•Ñ,D°D²D,Ñ,ÑCE Ñ•D²D¾Dµ D¼D½DµD½D,Dµ.**